

Complex Emotional Intelligence Learning Using Deep Neural Networks (Student Abstract)

Belainine Billal, Sadat Fatiha, Lounis Hakim

¹University of Quebec in Montreal
2098 Rue Kimberley, Montreal, QC H3C 3P8
Quebec, Canada
belainine.billal@courrier.uqam.ca

Abstract

Emotion recognition and mining tasks are often limited by the availability of manually annotated data. Several researchers have used emojis and specific hashtags as forms of training and supervision.

This research paper proposes a new textual and social corpus, the corpus labeled using basic emotions following Plutchik’s theory. Thus, This paper propose a first study for the representation and interpretation of complex emotional interactions, using deep neural networks.

Introduction

Several researchers proposed their approaches to express and recognize emotions, according to: (1) The intensity or valence, arousal, etc.(Posner, Russell, and Peterson, 2005). (2) The categorical model of the basic emotions. This model type proposes the detection of basic emotions that are considered as atomic and irreducible, or following a model established by (Plutchik, 1980), which represents a complex emotion as a combination of several basic emotions (De Bonis, 1996). The present research paper describes a study designed to detect complex emotions according to the model proposed by Plutchik. Our main contributions in this study are described as follows: (1) Introduction of a language model transfer to a multi-label classifier based on the architecture of the transformer decoder. (2) Introduction of a formal method for reading and interpreting complex emotions based on basic emotion vectors.

The Proposed Approach

Our proposed approach consists of creating an emotional classifier able to detect the eight basic emotions according to the Plutchik model. This classifier use conflicting emotion representation as an implicit rule, summed up by three main phases. First, we proceed by collecting the annotated data for the construction of corpus, by filtering and mixing several types of corpora in order to collect the eight of basic emotions. The second phase is the detection of emotional vector using four dimensions space. The third phase consists of interpreting and reading complex emotions.

Copyright © 2020, Association for the Advancement of Artificial Intelligence (www.aaai.org). All rights reserved.

Corpus :

Our training corpus is based on a combination and filtering of several datasets from several sources. We have broken down the complex emotions that existed in our corpus as: 1) *Love = Joy + Trust*. 2) *Shame = Fear + Disgust*. 3) *Guilt = Fear + Joy*.

Table 1: Sources of all used Corpora

Dataset	Labels
EmoTxt ¹	joy, anger, sadness, love, surprise, fear
PsychExp ²	joy, fear, anger, sadness, disgust, shame, guilt
DailyDialog ³	no emotion, anger, disgust, fear, happiness, sadness, surprise
NRC.Emotion.Lexicon. v0.92 ⁴ emotion_proposition_store ⁵	joy, fear, disgust, anger, sadness, surprise, trust and anticipation
WordNetAffect (Valitutti, 2004)	joy, fear, disgust, anger, sadness, surprise, trust and anticipation

These data contain the eight basic emotions according to Plutchik’s theory. In addition, there are three complex emotions that generally represent the complex emotions of our model.

Detecting and Reading complex emotions.

Our problem transformed into a multi-label learning problem where each of the four dimensions is represented by a label with three values (1.0, -1), each label detected by a Sequence to Vector model (Seq2vec). we mark 1 if the emotion is present and -1 if the inverse of the emotion is present. If the emotion with its inverse is absent, we mark 0. We use transfer learning of a DeepMoji model. We propose to define the number of dimensions of our basic space is four pairs of emotions and is formally defined by the base $B = ((\text{Joy, Sadness}), (\text{Trust, Disgust}), (\text{Fear, Anger}), (\text{Surprise, Anticipation}))$. Table 2 shows a representation of primary complex emotions (Primary dyads).

Table 2 is used as a transition matrix W to detect complex emotions for primary dyads.

¹<https://github.com/collab-uniba/EMTk>

²<https://github.com/bfelbo/DeepMoji/tree/master/data>

³<http://yanran.li/dailydialog>

⁴Lexicon of the NRC Word Emotion Association.

Table 2: Combinations of 2 adjacent emotions that make the primary dyads in 4 dimensions.

Advanced Emotions Primary Dyad	Anticipation-Surprise	Joy-Sadness	Trust-Disgust	Fear-Anger
Optimism	1	1	0	0
Love	0	1	1	0
Submission	0	0	1	1
Apprehension	-1	0	0	1
Disappointment	-1	-1	0	0
Remord	0	-1	-1	0
Contempt	0	0	-1	-1
Aggressiveness	1	0	0	-1

In equations 1 and 2, we show how one can detect the presence of a complex emotion by multiplying the matrix W by the vector V , which represents the coordinates of the emotions in our vector space (equation 1). We use same process to generate the transition matrix of Secondary dyads and Tertiary dyads.

$$S_{Primary\ Dyad} = W_{Primary\ Dyad} V \quad (1)$$

$$\begin{cases} Emotion_{complex} = \underset{i}{argmax}(S_i) \\ and \\ S_i \geq 1 \end{cases} \quad (2)$$

$i \in (Optimism=0, Love=1, Submission=2, Alarm=3, Disappointment=4, Contemptment=5, Remord=6, Aggressiveness=7)$

The result for the complex emotion obtained should be the result that maximizes a component of the vectors.

Equation 2 presents our objective function for reading the complex emotion. The complex emotions generated by the index i correspond to the emotions in the transition matrix W given in table 2.

Experiments and Analysis

We conducted one sets of experiments on four models. Each model has three classes (1,-1,0) that reflect one dimension of the emotion and its inverse, as well as the absence of both. Thus, four classifiers are proposed, as follows: *Joy/Sadness*, *Trust/Disgust*, *Anticipation/Surprise*, *Anger/Fear*.

The first set of experiments was based on the eight emotions as proposed in Plutchik’s model. In order to represent those emotions well, we converted the complex emotions that exist in the corpus using a composition of the basic emotions.

Table 3: Results of Recall, Precision, F-score for different classifiers after using transfer learning.

Axis Emotions	Recall	Precis	F1	Macro F1	Exact Match
joy/sadness	0.56	0.44	0.49	0.54	0.43
anger/fear	0.61	0.56	0.58		
surprise/anticipation	0.55	0.51	0.52		
trust/disgust	0.63	0.59	0.57		

The table 4 presents a comparison with the state of the art for public datasets that contains some complex emotions. *EmoTxt* with a test that contains 200 instances of the labels

Table 4: Results based on Exact Match, F-score for Love, Guilt and Shame classification after using transfer learning.

Model	Complex Emotion	Average-F1	Exact Match
Our Model	Love (Joy + Trust)	0.58	0.52
	Shame (Fear + Disgust)	0.54	0.53
	Guilt (Fear + Joy)	0.54	0.51
Model	Complex Emotion	F1	Accuracy
DeepMojji(PsychExp)	Shame	0.56	0.59
	Guilt	0.54	0.60
Model	Complex Emotion	F1	Accuracy
DeepMojji (PsychExp + EmoTxt)	Love	0.57	0.63
	Shame	0.53	0.58
	Guilt	0.51	0.58

’Love’ and *PsychExp* with a test that contains 264 instances of labels *Guilt* and 427 *Shame*. then we used the DeepMojji model Felbo et al. with a *PsychExp* dataset, but for the second we added the *Love* label to the model after training with *PsychExp* and *EmoTxt* dataset. The *Love* label represents the *Joy + Trust* detection found in the Primary Dyads, the *Shame* label represents the ’*Fear + Disgust*’ detection found in the Secondary Dyads, the *Guilt* label represents the ’*Fear + Joy*’ detection that is in the Tertiary Dyads.

By analyzing our results in table 4, we can notice a slight difference between the different experiments.

The average F1 score of our model for label *Guilt* is equal to the F1 score of the experiment done by the DeepMojji model (PsychExp), but the DeepMojji model accuracy exceeds Exact match of our model by 0.07, because the exact match means that both labels detect it at the same time.

Our model is better in terms of average F1 score for the label *Love* (*Trust + Joy*) compared to the DeepMojji (PsychExp + EmoTxt) model F1-score which contains the *Love* label.

Conclusions and perspectives

This research paper presents a novel approach for the detection of complex emotions, according to the Plutchik model and using multi-label classifiers. These classifiers are divided into 4 multiclass classifiers. The main contribution is the representation of complex emotions according to the Plutchik theory, in a vector space with four axes.

Due to the nature of social media text, some emotions, such as fear and disgust, are under-represented in the datasets. Also, other emotions, like anticipation, are absent.

References

- De Bonis, M. 1996. *Connaître les émotions humaines*, volume 212. Editions Mardaga.
- Felbo, B.; Mislove, A.; Sogaard, A.; Rahwan, I.; and Lehmann, S. Using millions of emoji occurrences to learn any-domain representations for detecting sentiment, emotion and sarcasm.
- Plutchik, R. 1980. Emotion: A psychoevolutionary analysis. *Nueva York: Harper and Row*.
- Posner, J.; Russell, J. A.; and Peterson, B. S. 2005. The circumplex model of affect: An integrative approach to affective neuroscience, cognitive development, and psychopathology. *Development and Psychopathology* 17(3):715–734.
- Valitutti, R. 2004. Wordnet-affect: an affective extension of wordnet. In *In Proceedings of the 4th International Conference on Language Resources and Evaluation*, 1083–1086.